



CL420

Clamp-on Process Meter

**Measure 4 to 20mA
DC signals without
breaking the loop!**

Features:

- 0.2% Accuracy, 0.01mA Resolution
- Dual Display
- LED Torch Light, Backlight Display
- Analog Output Available



Actual size





CL420 Clamp-on Process Meter

● Product Model Code

Name	Model
Clamp-on Process Meter	CL420

● Standard Accessories (supplied)


Name	Model
Soft case	93045

● Optional Accessories (sold separately)

Name	Model
Output cable (banana plug)	98076
Output cable (for screw terminal)	98077

External dimensions

unit: mm



Specifications

Model	CL420	
Diameter of measurable conductor	6mm diameter max.	
DC Current	Range and resolution [Range]	Accuracy ¹
	20 mA: 0.00 to ±21.49mA 100 mA: ±21.0 to ±126.0mA	±(0.2%rdg+5dgt) ² ±(1.0%rdg+5dgt)
DC Voltage OUTPUT [10mV/mA]	20 mA: 0.0 to ±214.9mV 100 mA: ±210 to ±1260mV	(DCA Accuracy)+(±0.5mV) (DCA Accuracy)+(±3mV)
Display	4-digit LCD Numeric display	
Response time	Approx. 1.5 seconds (2.5 seconds when across the range)	
Range switching	Auto range	
Operating temperature and humidity	-10°C to +50°C 80% RH or less (no condensation)	
Safety Standards	EN61010-1, EN61010-2-030, EN61010-2-032	
Withstanding voltage	2.21kV AC for 5 seconds (between the core and the case)	
Power supply	Four AA-size alkaline batteries (1.5V LR6)	
Battery life	Approx. 60hrs (continuous) backlight off and LED light off	
Other functions	Data hold, Zero adjust function, Auto power off, LED Torch light, Back light display, Illuminant panel	
External dimensions and weight	61 (W) × 111 (H) × 40 (D) mm Approx. 290g (including batteries)	
Standard accessories	User's Manual, Batteries, Soft case (93045)	

¹ At 23°C ±5°C, 75% RH or less

Measurement accuracy: ±(% of reading + digits)

Terms of accuracy: Open and close the clamp sensor after power on and perform zero adjustment.


² The 20mA range accuracy assurance is the average of 5 times measuring.

Examples of Analog Output Application

Example of 98076 output cable connecting to TY530



Example of 98077 output cable for screw terminal connecting to a data logger




Accessories (sold separately)

Accessories (supplied)



Output cable
Model: 98076



Output cable (for screw terminal)
Model: 98077



Soft case for CL420
Model: 93045

Related Products



Pressure Calibrator
CA700



Multi-functional Calibrator
CA150



Multi-functional Calibrator
CA71



Process Multimeter
CA450

CAUTION



• Read the product manual before using this product to ensure safe use.



绿测科技有限公司

广州总部：广州市番禺区陈边村金欧大道83号江潮创意园A栋208室

深圳分公司：深圳市龙华区龙华街道 油松社区东环一路1号耀丰通工业园1-2栋2楼607

南宁分公司：广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号

广州分公司：广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房

电话：020-2204 2442

传真：020-8067 2851

邮箱：Sales@greentest.com.cn

官网：www.greentest.com.cn



微信视频号



绿测科技订阅号



绿测工场服务号